

Item Nr.	EAN Code	Description	Watt	Volt
140301	8719743906273	Underfloor heating cable 5 mm.	300	230
140501	8719743906280	Underfloor heating cable 5 mm.	500	230
141001	8719743906297	Underfloor heating cable 5 mm.	1000	230
141201	8719743906303	Underfloor heating cable 5 mm.	1200	230
141601	8719743906310	Underfloor heating cable 5 mm.	1600	230
141801	8719743906327	Underfloor heating cable 5 mm.	1800	230
142001	8719743906334	Underfloor heating cable 5 mm.	2000	230
142401	8719743906341	Underfloor heating cable 5 mm.	2400	230
142801	8719743906358	Underfloor heating cable 5 mm.	2800	230
143201	8719743906365	Underfloor heating cable 5 mm.	3200	230

Ohm	Ampère
176	1.3
106	2.2
53	4.3
44	5.2
33	7.0
29	7.8
26	8.7
22	10.4
19	12.2
17	13.9

Heating Cable:
* Heating Conductor
* Insulation
* Drain Wire
* Shielding
* Outer Jacket
* Cable dia.
* Cold Tail:
* Conductor
* Core insulation
* Drain Wire
* Shielding
* Outer Jacket
* Cable dia.
* Cold Tail length
Connection : Hot Cable to Supply Cable
Splice :
End :
* Electrical Parameters
* Power Supply
* Linear Wattage

Solid (Both Heating)

XLPE

Multi-strand

Polyester laminated Aluminium Foil with Drain Wire

High Temperature PVC (105°C)

5.0 mm (Approx.)

AWG21, AWG19 & AWG14 X 2 Core Multi-Strand ATC

XLPE

Solid/Multi-strand ATC

Polyester laminated Aluminium Foil with Drain Wire

High Temperature PVC (105°C)

6.5 mm (Approx.)

3.5 Meters

Line connector crimped & covered by HST

Line connector crimped & covered by HST

230V, 60 Hz

20 W/m